


*Power You Can
Depend On*



HG-GEL Series

Valve Regulated Lead Acid



WWW.CDTROJAN.CN

HG-GEL Series

G-GEL Series

Valve Regulated

Lead Acid Battery – Gel Type



Applications

- Telecommunication systems
- Uninterruptible power supplies
- Electric Power Systems
- Electronic test equipment
- Control equipment
- Medical equipment
- Fire & security systems
- Solar systems
- Wine energy systems
- Other standby, cyclic and outdoor applications



Features and benefits

- Design life: 18 years (2V)
15 years (12V)
- Gel electrolyte technology for better wide temperature range performance, prevention from thermal runaway, insure reliability and safety
- Proprietary Pb-Ca Alloy - minimizing grid growth, reducing gassing, and extending battery life
- Flame arresting one-way pressure vents for safety and improved life
- Gas recombination efficiency of up to 99% for freedom from electrolyte maintenance
- Good deep cycle performance
- Lower self-discharge rate (Less than 3% per month)
- Not restricted for air transport - Complies with IATA/ICAO Special Provision A67
- Not restricted for surface transport - classified as non-hazardous material as related to DOT-CFR Title 49 parts 171-189
- Not restricted for water transport - classified as non-hazardous material per IMDG Amendment 27
- Manufactured in accordance with ISO 9001, ISO 14001, and ISO 45001
- Designed to be compliant with international standard IEC 60896-21/22

Specifications

Model	V	Capacity/Ah, C20,1.75EPV, 25°C	Capacity/Ah, C10,1.80EPV, 25°C	Weight/Kg	Dimensions(mm)				IEC Resistance (mΩ)	Terminal Type (Bolt)
					L	W	H	TH		
C&D 12-55HG	12	57.8	55	20.7	350	167	179	179	9.2	Insert(M6)
C&D 12-75HG	12	75.6	72	26.5	306	169	210	215	7.5	Insert(M6)
C&D 12-90HG	12	94.6	90	29.5	330	171	215	222	7.0	Insert(M6)
C&D 12-100HG	12	110	105	35.5	410	176	225	225	6.5	Insert(M8)
C&D 12-120HG	12	126	120	43.0	482	170	241	241	6.0	Insert(M8)
C&D 12-135HG	12	138	135	44.3	482	170	241	241	6.0	Insert(M8)
C&D 12-160HG	12	171	160	59.0	530	207	215	220	5.8	Insert(M8)
C&D 12-180HG	12	188	180	62.0	522	238	218	223	5.5	Insert(M8)
C&D 12-200HG	12	210	200	70.0	520	269	203	208	4.5	Insert(M8)
C&D 12-220HG	12	226	220	72.5	520	269	220	225	4.0	Insert(M8)
C&D 2-200HG	2	214	200	14.8	171	111	329	342	0.85	Insert(M8)
C&D 2-300HG	2	322	300	19.3	171	151	329	342	0.75	Insert(M8)
C&D 2-400HG	2	428	400	28.0	211	176	329	342	0.80	Insert(M8)
C&D 2-500HG	2	536	500	32.0	241	173	329	342	0.70	Insert(M8)
C&D 2-600HG	2	642	600	40.0	301	175	331	342	0.60	Insert(M8)
C&D 2-800HG	2	856	800	53.5	410	175	330	342	0.55	Insert(M8)
C&D 2-1000HG	2	1070	1000	63.5	475	175	330	342	0.60	Insert(M8)
C&D 2-1500HG	2	1606	1500	105	400	350	345	367	0.60	Insert(M8)
C&D 2-2000HG	2	2140	2000	132	476	337	330	342	0.60	Insert(M8)

Operating Temperature Range	-20°C to 60°C
Nominal Operating Temperature Range	23°C - 27°C
Float Charging Voltage	12V: 13.38 to 13.62 VDC per unit @25°C 2V: 2.23 to 2.27 VDC per unit @25°C
Recommended Maximum Charging Current Limit	C/5 Amperes@ 20hr rate
Equalize charge and cycle service voltage	12V: 14.4 to 14.7 VDC per unit @25°C 2V: 2.40 to 2.45 VDC per unit @25°C
Self Discharge	Batteries can be stored for 4 months at 25°C. Batteries stored at temperatures greater than 25°C will require recharge sooner. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Container Material	ABS (UL94 V-0)

TECHNOLOGIES

Contact us

Headquarters

C&D Technologies, Inc.
200 Precision Road
Horsham, PA 19044 USA

Europe

C&D Technologies (UK) Limited
Unit 25, Romsey Industrial Estate, Greatbridge Road
ROMSEY, Hampshire, SO51 0HR, UK
Office: +44 (0) 1794 518 173
E-mail: Gdailly@cdtrojan.com

Middle East & Africa

C&D TECHNOLOGIES (UK) LIMITED
LOB 15 – OFFICE 413
PO BOX 263116
JEBEL ALI FREE ZONE
DUBAI – UNITED ARAB EMIRATES
PH: +971 5045 494 79
E-mail: phockings@cdtrojan.com

C&D Tech Power Solutions (India) Private Limited

Tel: (91)97 6705 8489
E-mail: rsingh@cdtrojan.com.cn

C&D Technologies (Hong Kong) Ltd.

Tel: (852) 2119 9870
Fax: (852) 2117 0342
E-mail: Bhui@cdtrojan.com

C&D Tech (Singapore) Pte Ltd.

Tel: (65) 6291 1031
Fax: (65) 6291 0767
E-mail: Bhui@cdtrojan.com

C&D Trojan (Shanghai) Energy Technologies Co., Ltd.

Tel: 400-678-3721

C&D Trojan (Shanghai) Power Technologies Co., Ltd.

No.55 Liandu Road, Spark Development Zone, Shanghai, China
Tel: (86) 21 3711 1222

C&D Jiangsu Technologies Co., Ltd.

Circular Economy Industrial Park
Pizhou High-tech Industrial Development Zone,
Jiangsu Province China 221300
Tel: (86) 516 8687 9857

Website

www.cdtrojan.cn

China Service Hotline: 400-678-3721

C&D reserves the right to revise the data and information provided in this catalogue.