

*Power You Can
Depend On*



LBTY 2V Series

Valve Regulated Lead Acid

—— *Wider Range & Higher Capacity*



WWW.CDTROJAN.CN

LBTY 2V Series

LBTY 2V series

Valve Regulated Lead Acid Battery For Standby Power Applications



Applications

- Telecom control system
- Uninterrupted Power Supply (UPS)
- Metro and assistant system
- Marine equipment
- Electric power systems
- Power plant
- Hospital and medical equipment
- Fire alarm applications
- Alarm and safety system

Features

- Design life:15 years
- High quality design insurance
- Pb-Ca Alloy for positive plate grid
- Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance
- Lower self-discharge rate (about 3% per month @25°C)
- UL-recognized component
- Flame retardant container materials,complied with materials UL94 V-0
- Not restricted for air transport-Complies with IATA/ICAO Special Provisions A67
- Not restricted for surface transport - Classified as non-hazardous material as related to DOT-CFR 49 Title 49 parts 171-189
- Not restricted for water transport - Classified as non-hazardous material per IMDG Amendment 27
- Manufactured in accordance with ISO 9001, ISO 14001, and ISO 45001
- Designed to be compliant with international standard IEC 60896-21/22

Specifications

Model	V	Capacity/Ah (C10,1.80V@25°C)	Dimensions (mm)				Weight / Kg	Terminal Type(Bolt)	Resistance/ mΩ
			L	W	H	TH			
C&D2-200LBT	2	200	170	106	330	345	12.4	Insert(M10)	0.74
C&D2-300LBT	2	300	170	150	330	345	17.8	Insert(M10)	0.56
C&D2-400LBT	2	400	196	171	330	345	23.6	Insert(M10)	0.48
C&D2-500LBT	2	500	241	171	330	345	29.8	Insert(M10)	0.38
C&D2-600LBT	2	600	286	171	330	345	35.6	Insert(M10)	0.37
C&D2-800LBT	2	800	383	171	330	345	47.7	Insert(M10)	0.34
C&D2-1000LBT	2	1000	471	171	330	345	59.5	Insert(M10)	0.30
C&D2-1200N LBT	2	1200	471	171	330	345	72.0	Insert(M10)	0.29
C&D2-1500N LBT	2	1500	336	288	330	345	86.5	Insert(M10)	0.28
C&D2-2000LBT	2	2000	476	337	330	345	119.0	Insert(M10)	0.26
C&D2-2500N LBT	2	2500	476	337	330	345	143.0	Insert(M10)	0.24
C&D2-3000LBT	2	3000	590	362	383	383	176.0	Insert(M8)	0.20

*Batteries to be mounted with 15mm spacing minimum and free air ventilation.


All dimensions are for reference only. Specifications subject to change without notification.

The design life listed indicates the service life under ideal service conditions. Changes in service conditions do not affect the design life, but the actual service life may be shorter than the design life.

Specifications

Operating Temperature Range with Temperature Compensation	Discharge: -40°C to 50°C Charge: -20°C to 50°C Storage: -20°C to 40°C
Nominal Operating Temperature Range	25°C±2°C
Float Charging Voltage	2.23 to 2.27V per cell average at 25°C
Equalization and Cycle Service Charging Voltage	2.35 to 2.4V per cell average at 25°C
Self Discharge	Battery may be stored for up to 4 months at 25°C, and self-discharge ratio less than 3% per month at 25°C. Please charge the batteries before using.
Accessories (optional)	Inter unit connectors, racks and cabinet systems are available
Terminal	Thread inserted terminal to accept M10 bolt
Container materials	ABS(UL 94 V-0)

Product Dimensions



TECHNOLOGIES

Contact us

Headquarters

C&D Technologies, Inc.
200 Precision Road
Horsham, PA 19044 USA

Europe

C&D Technologies (UK) Limited
Unit 25, Romsey Industrial Estate, Greatbridge Road
ROMSEY, Hampshire, SO51 0HR, UK
Office: +44 (0) 1794 518 173
E-mail: Gdailly@cdtrojan.com

Middle East & Africa

C&D TECHNOLOGIES (UK) LIMITED
LOB 15 – OFFICE 413
PO BOX 263116
JEBEL ALI FREE ZONE
DUBAI – UNITED ARAB EMIRATES
PH: +971 5045 494 79
E-mail: phockings@cdtrojan.com

C&D Tech Power Solutions (India) Private Limited

Tel: (91)97 6705 8489
E-mail: PT@cdtrojan.com

C&D Technologies (Hong Kong) Ltd.

Tel: (852) 2119 9870
Fax: (852) 2117 0342
E-mail: Bhui@cdtrojan.com

C&D Tech (Singapore) Pte Ltd.

Tel: (65) 6291 1031
Fax: (65) 6291 0767
E-mail: Bhui@cdtrojan.com

C&D Trojan (Shanghai) Energy Technologies Co., Ltd.

Tel: 400-678-3721

C&D Trojan (Shanghai) Power Technologies Co., Ltd.

No.55 Liandu Road, Spark Development Zone, Shanghai, China
Tel: (86) 21 3711 1222

C&D Jiangsu Technologies Co., Ltd.

Circular Economy Industrial Park
Pizhou High-tech Industrial Development Zone,
Jiangsu Province China 221300
Tel: (86) 516 8687 9857

Website

www.cdtrojan.cn

China Service Hotline: 400-678-3721

C&D reserves the right to revise the data and information provided in this catalogue.